

# Installasjonskabel

## PR, ulimt skjerm



### Bruksområde

<b>Bruksområde</b>	Husinstallasjonskabel til fast opplegg innen- og utendørs.
<b>Ledertemperatur</b>	Max. 70°C
<b>Kortslutningstemperatur</b>	Max. 160°C
<b>Håndteringstemperatur</b>	Min. 10°C
<b>Lagertemperatur</b>	Max. 40°C





### Konstruksjon

<b>Leder</b>	Entrådet, glødd kobberleder
<b>Isolasjon</b>	Blyfri PVC
<b>Leder-merking</b>	Blå, brun
<b>Fyllkappe</b>	Plast
<b>Jordleder</b>	Blank kobberleder
<b>Metalkappe</b>	Aluminiumsbånd
<b>Ytre kappe</b>	Blyfri PVC
<b>Kapfefarge</b>	Hvit



### Teknikk

<b>Standard</b>	NEK 535, IEC 60332-1/EN 50265
<b>Driftspenning</b>	300/500V
<b>Prøvespenning</b>	2,5 kV AC
<b>CE-merket</b>	LVD

### N05VA5VH2-U

Dimensjon	Leder Antall tråder og diameter	Levering	Ytre diameter nom.	Ca. vekt	EI- nr.	EAN- nr.
mm <sup>2</sup>	mm	m	mm	kg pr. km		
2X1,5/1,5	1 x 1,36	B/50	5,9 x 8,2	90	1056100	
2X1,5/1,5	1 x 1,36	T/500	5,9 x 8,2	90	1056110	
2X2,5/2,5	1 x 1,76	B/50	6,9 x 9,6	124	1056103	
2X2,5/2,5	1 x 1,76	T/450	6,9 x 9,6	124	1056113	







### N05VA5V-U

Dimensjon	Leder Antall tråder og diameter	Levering	Ytre diameter nom.	Ca. vekt	EI- nr.	EAN- nr.
mm <sup>2</sup>	mm	m	mm	kg pr. km		
3X1,5/1,5	1 x 1,36	B/50	8,5	134	1056101	
3X1,5/1,5	1 x 1,36	T/350	8,5	134	1056111	

# Installasjonskabel

## PR, ulimt skjerm

### N05VA5V-U

Dimensjon	Leder Antall tråder og diameter	Levering	Ytre diameter nom.	Ca. vekt	EI- nr.	EAN- nr.
mm <sup>2</sup>	mm	m	mm	kg pr. km		
4X1,5/1,5	1 x 1,38	B/50	12,5	157	1056102	 7 071242 000083
4X1,5/1,5	1 x 1,38	T/250	12,5	157	1056112	 7 071242 000090
3X2,5/2,5	1 x 1,76	B/50	10,3	196	1056104	 7 071242 000168
3X2,5/2,5	1 x 1,76	T/250	10,3	196	1056114	 7 071242 000175
2X4/4	1 x 2,26	B/50	10,9	228	1056106	 7 071242 000243
2X4/4	1 x 2,26	T/250	10,9	228	1056116	 7 071242 000250