

# Installasjonskabel

## PR brun, limt skjerm



### Bruksområde

<b>Bruksområde</b>	Husinstallasjonskabel til fast opplegg innen- og utendørs.
<b>Ledertemperatur</b>	Max. 70°C
<b>Kortslutningstemperatur</b>	Max. 160°C
<b>Håndteringstemperatur</b>	Min. 10°C
<b>Lagertemperatur</b>	Max. 40°C



### Konstruksjon

<b>Leder</b>	Entrådet, glødd kobberleder
<b>Isolasjon</b>	Blyfri PVC
<b>Leder-merking</b>	Blå, brun
<b>Fyllkappe</b>	Plast
<b>Jordleder</b>	Blank kobberleder
<b>Metalkappe</b>	Aluminiumsbånd (Limt til ytterkappe)
<b>Ytre kappe</b>	Blyfri PVC
<b>Kappefarge</b>	Brun




### Teknikk

<b>Standard</b>	NEK 535, IEC 60332-1/EN 50265
<b>Driftspenning</b>	300/500V
<b>Prøvespenning</b>	2,5 kV AC
<b>CE-merket</b>	LVD

### N05VA5VH2-U

Dimensjon	Leder Antall tråder og diameter	Levering	Ytre diameter nom.	Ca. vekt	EI-nr.	EAN-nr.
mm <sup>2</sup>	mm	m	mm	kg pr. km		
2X1,5/1,5	1 x 1,36	B/50	5,8 x 8,2	90	1056220	
2X2,5/2,5	1 x 1,76	B/50	6,8 x 9,5	124	1056223	

### N05VA5V-U

Dimensjon	Leder Antall tråder og diameter	Levering	Ytre diameter nom.	Ca. vekt	EI-nr.	EAN-nr.
mm <sup>2</sup>	mm	m	mm	kg pr. km		
3X1,5/1,5	1 x 1,36	B/50	8,4	134	1056221	
4X1,5/1,5	1 x 1,36	B/50	10,4	157	1056222	
3X2,5/2,5	1 x 1,76	B/50	10,2	196	1056224	
2X4/4	1 x 2,26	B/50	10,8	228	1056225	